

# Drinking Water Cooler Specifications/ Alpine™ Alternative™ model 6700K

| ITEM              |                       | Stainless      | Removable   | Stainless   | Removable   |      |
|-------------------|-----------------------|----------------|---|-------------|-------------|------|
| Type              |                       | Hot & Cold     | Hot & Cold  | Cook & Cold | Cook & Cold |      |
| Rating Power      |                       | 120V AC / 60Hz |   |             |             |      |
| Standard Current  | Cold                  | 1.5 A          |   |             |             |      |
|                   | Hot                   | 3.5 A          |   | -           |             |      |
| Power Consumption | Cold                  | 110 W          |   | -           |             |      |
|                   | Hot                   | 450 W          |   | -           |             |      |
| Cooling System    | Compressor            |                | Single Phase Motor(1/15HP)                                    |             |             |      |
|                   | Refrigerant           |                | R-134a(35g)   |             |             |      |
|                   | Temperature Control   |                | Thermostat(GNF-135SG)   |             |             |      |
|                   | Temperature Range     |                | 37°F to 41°F  |             |             |      |
|                   | Tank Metal            |                | SUS304  | HDPE        | SUS304      | HDPE |
|                   | Tank Capacity         |                | 40 six-ounce cups per hour < 50°F/ 3.25qts cold/ 1.3qts room. |             |             |      |
| Heating System    | Heater                |                | Band Heater(HK-450)   |             | -           |      |
|                   | Temperature Control   |                | Bimetal(Auto 163°F/181°F)                                     |             | -           |      |
|                   | Temp Control Range    |                | (181°F±41°F)  |             | -           |      |
|                   | Safety Device         |                | Bimetal(Manual Reset 239°F)                                   |             | -           |      |
|                   | Tank Metal            |                | SUS304  |             |             | -    |
|                   | Tank Capacity         |                | 30 six-ounce cups per hour > 158°F with 1.75 qt. storage tank |             |             |      |
| Dimension (W*D*H) | Product               |                | 12.75"x 39.00"  |             |             |      |
|                   | Packed(approximately) |                | 12.5"x 13"x 39.75"  |             |             |      |
| Weight            | Product               |                | 40.00lbs  |             | 37.70lbs    |      |
|                   | Packed(approximately) |                | 40.80lbs  |             | 38.50lbs    |      |